

## MP 600 - Teknik Özellikler



### Description

MP 600, teleskopik yükleyiciler ve uygulamalı makineler kullanılan belediye/bakım operasyonları için uygun, konforlu bir sürüş deneyimi sağlayan bir tarımsal sanayi lastiğidir. Bu lastik, uzun bir kullanım ömrü ile birlikte iyi çekiş ve mükemmel kendi kendini temizleme özellikleri sunar.

### UM

US Standard

### Construction

BIAS

### Machinery

Zirai: Uygulamalı makine • Teleskopik yükleyici  
Endüstriyel: Teleskopik yükleyici • Genel kullanım aracı / Kompaktör

Version	SPECIAL
Type	TL
Tyre Size	400/70 - 24 (16.0/70 - 24)

## Dimensions US Standard

Usa code	94051618
Ply Rating	14
Section Width (inch)	15.9
Overall Diameter (inch)	46.7
Static Loaded Radius (inch)	21.5
Rolling Circumference (inch)	139
Rim Rec	13 SDC
Rim Alt	12

## Load capacity (lbs)

mph / psi	51
25 DW	8050
30 DW	7830

Printed on 4/27/2024 5:49 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..