

## MT 612 - Teknik Özellikler



### Description

MT 612 yolda ve arazide çok amaçlı kullanım için özel olarak tasarlanmıştır. Güçlü gövdesi ağır yükleri yüksek hızda taşımaya imkan verirken geniş çekmeleri olağanüstü çekiş sağlar. Ekstra sırt genişliği kumda ve çamurda kusursuz flotasyon sunar.

### UM

International Standard

### Construction

BIAS

### Machinery

Zirai: Römork

Endüstriyel: Genel kullanım aracı / Kompaktor

Version	STANDARD
Type	TT
Tyre Size	14.00 - 20

## Dimensions International Standard

Ply Rating	22
Section Width (mm)	390
Overall Diameter (mm)	1265
Static Loaded Radius (mm)	594
Rolling Circumference (mm)	3827
Rim Rec	10

## Load capacity (Kg)

km/h / bar	8.60
80 LS	5300
80 LD	4750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/7/2024 9:37 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..