

MT 612 - Teknik Özellikler



Description

MT 612 yolda ve arazide çok amaçlı kullanım için özel olarak tasarlanmıştır. Güçlü gövdesi ağır yükleri yüksek hızda taşımaya imkan verirken geniş çekmeleri olağanüstü çekiş sağlar. Ekstra sırt genişliği kumda ve çamurda kusursuz flotasyon sunar.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Römork

Endüstriyel: Genel kullanım aracı / Kompaktor

Version	STANDARD
Type	TT
Tyre Size	14.00 - 20

Dimensions International Standard

Ply Rating	20
Section Width (mm)	390
Overall Diameter (mm)	1265
Static Loaded Radius (mm)	594
Rolling Circumference (mm)	3827
Rim Rec	10
ECE	E11-54R-0021125

Load capacity (Kg)

km/h / bar	7.60
80 LS	4875
80 LD	4375

Printed on 4/19/2024 9:35 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..