MULTIMAX MP 513 - Teknik Özellikler

Description

MULTIMAX MP 513, BKT tarafından belediye/bakım ve taşıma uygulamalarındaki çok amaçlı araçlar için hem tarımsal hem de endüstriyel kullanım için tasarlanmıştır. Genel kullanım araçları ve gübre kamyonları için mükemmeldir. Güçlü çelik kuşaklı naylon gövde sayesinde MULTIMAX MP 513, ağır yüklerin yüksek hızlarda taşınmasını ve konforlu bir sürüş deneyimi sağlar. Üstün kendi kendini temizleme özellikleriyle birlikte daha uzun kullanım ömrü ve çekiş sağlar.

UM

US Standard

Construction

RADIAL

Machinery

Zirai: Genel kullanım aracı • Gübre kamyonu
Endüstriyel: Genel kullanım aracı / Kompaktor

Version	STANDARD
Type	TL
Tyre Size	425/75 R 20 MPT
LI/SS	148 G

Dimensions US Standard

Usa code	94034703
Section Width (inch)	16.6
Overall Diameter (inch)	45.1
Static Loaded Radius (inch)	20.5
Rolling Circumference (inch)	137
Rim Rec	13
Rim Alt	13 SDC ; 11 SDC ; 12 SDC ; 11 ; 12
ECE	E11-54R-0016141

Load capacity (lbs)

mph / psi	23	29	36	44	51	58
55	3390	3990	4740	5490	6220	6940
40	3690	4330	5150	5960	6750	7540
25	3910	4600	5460	6320	7150	7990

Printed on 4/29/2024 3:31 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..