

## MULTIMAX MP 515 - Teknik Özellikler



### Description

MULTIMAX MP 515 genel kullanım araçları ve gübre kamyonları için tasarlanmış, radyal bir tarımsal sanayi lastiğidir. Belediye ve taşıma uygulamaları için uygundur. Lastik, yolda üstün sürüş konforu ve mükemmel kendi kendini temizleme özellikleri ile mükemmel çekiş sağlayan benzersiz bir sırt tasarımına sahiptir. Güçlü çelik kuşaklı naylon gövde ve güçlendirilmiş omuz olağanüstü dayanıklılık sağlar. MULTIMAX MP 515 yüksek hızlar (90 km/sa.) için de mükemmel lastiktir.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Zirai: Genel kullanım aracı • Gübre kamyonu

Version	STANDARD
Type	TL
Tyre Size	405/70 R 20 MPT
LI/SS	136 G

## Dimensions International Standard

Section Width (mm)	407
Overall Diameter (mm)	1076
Static Loaded Radius (mm)	493
Rolling Circumference (mm)	3286
Rim Rec	13
Rim Alt	13 SDC ; 12 SDC ; 11 SDC ; 11
ECE	E4-54R-0016565

## Load capacity (Kg)

km/h / bar	1.6	2.0	2.5	3.0	3.5
90	1340	1580	1820	2040	2240
65	1455	1715	1975	2215	2435
40	1545	1820	2095	2350	2580

Printed on 4/25/2024 11:17 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..