

MULTIMAX MP 515 - Teknik Özellikler



Description

MULTIMAX MP 515 genel kullanım araçları ve gübre kamyonları için tasarlanmış, radyal bir tarımsal sanayi lastiğidir. Belediye ve taşıma uygulamaları için uygundur. Lastik, yolda üstün sürüş konforu ve mükemmel kendi kendini temizleme özellikleri ile mükemmel çekiş sağlayan benzersiz bir sırt tasarımına sahiptir. Güçlü çelik kuşaklı naylon gövde ve güçlendirilmiş omuz olağanüstü dayanıklılık sağlar. MULTIMAX MP 515 yüksek hızlar (90 km/sa.) için de mükemmel lastiktir.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Genel kullanım aracı • Gübre kamyonu

Version	STANDARD
Type	TL
Tyre Size	405/70 R 20 MPT
LI/SS	136 G

Dimensions US Standard

Usa code	94056545
Section Width (inch)	16
Overall Diameter (inch)	42.4
Static Loaded Radius (inch)	19.4
Rolling Circumference (inch)	129.4
Rim Rec	13
Rim Alt	13 SDC ; 12 SDC ; 11 SDC ; 11
ECE	E4-54R-0016565

Load capacity (lbs)

mph / psi	23	29	36	44	51
55	2950	3480	4010	4500	4940
40	3210	3780	4350	4880	5370
25	3410	4010	4620	5180	5690

Printed on 4/25/2024 6:40 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..