

## MULTIMAX MP 519 - Teknik Özellikler



### Description

MULTIMAX MP 519 tüm taşıma uygulamalarında kullanılan kamyonetler için özellikle uygundur. Çelik kuşaklı gövde yüksek hızda (90 km/sa. - 60 mil/sa.) mükemmel denge sağlar. Lastik, düşük yuvarlanma direnci sayesinde daha az yakıt tüketimi sağlar.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Endüstriyel: Kamyonet

Version	STANDARD
Type	TL
Tyre Size	7.50 R 16 LT
LI/SS	112/110G

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	220
Overall Diameter (mm)	810
Static Loaded Radius (mm)	377
Rolling Circumference (mm)	2449
Rim Rec	6.00
Rim Alt	5.50 F ; 6 L ; 7 L
ECE	E11-54R-0019046

## Load capacity (Kg)

km/h / bar	3.5
90 LS	1120
90 LD	1060

Printed on 4/19/2024 2:04 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..