

## MULTIMAX MP 519 - Veri Sayfasını İndir



### Description

MULTIMAX MP 519 tüm taşıma uygulamalarında kullanılan kamyonetler için özellikle uygundur. Çelik kuşaklı gövde yüksek hızda (90 km/sa. - 60 mil/sa.) mükemmel denge sağlar. Lastik, düşük yuvarlanma direnci sayesinde daha az yakıt tüketimi sağlar.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Endüstriyel: Kamyonet

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
7.50 R 16 LT	STANDARD	109/107 G	6	6.00	5.50 F ; 6 L ; 7 L	220	810	377	2449	TL	
7.50 R 16 LT	STANDARD	112/110G	8	6.00	5.50 F ; 6 L ; 7 L	220	810	377	2449	TL	E11-54R-0019046

Printed on 4/19/2024 2:33 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..