

## MULTIMAX MP 527 - Teknik Özellikler



### Description

MULTIMAX MP 527 tarımsal sanayi uygulamalarında teleskopik yükleyiciler ve küçük yükleyiciler için tasarlanmış çok amaçlı bir radyal lastiktir. Lastik, daha sert yüzeylerde bile mükemmel çekiş sağlayan bir blok diş deseni tasarımına sahiptir. Güçlü yanak, kaldırma modunda olağanüstü sabitleme sağlar. MULTIMAX MP 527, kesilme ve kopmaya karşı dirençli özel bir hamura ve uzun bir kullanım ömrüne sahiptir.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Zirai: Küçük yükleyici • Teleskopik yükleyici  
Endüstriyel: Küçük yükleyici • Teleskopik yükleyici

|           |                 |
|-----------|-----------------|
| Version   | STANDARD        |
| Type      | TL              |
| Tyre Size | 340/80 R 20 IND |
| LI/SS     | 144 A8/B        |

## Dimensions International Standard

|                            |                                  |
|----------------------------|----------------------------------|
| Section Width (mm)         | 343                              |
| Overall Diameter (mm)      | 1052                             |
| Static Loaded Radius (mm)  | 483                              |
| Rolling Circumference (mm) | 3176                             |
| SRI (mm)                   | 500                              |
| Rim Rec                    | 11                               |
| Rim Alt                    | W10 ; 11 SDC ; W11 ; 12 ; 12 SDC |
| ECE                        | E11-106R-003957                  |

## Load capacity (Kg)

| km/h / bar | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.5  | 4.0  | 4.2  | 4.4  |
|------------|------|------|------|------|------|------|------|------|------|
| 50         | 1345 | 1600 | 1820 | 2075 | 2325 | 2495 | 2800 | -    | -    |
| 40         | 1345 | 1600 | 1820 | 2075 | 2325 | 2495 | 2800 | -    | -    |
| 30         | 1440 | 1710 | 1950 | 2220 | 2490 | 2670 | 3000 | -    | -    |
| 25         | 1495 | 1775 | 2025 | 2305 | 2585 | 2770 | 3110 | -    | -    |
| 10 Cyc.    | 1640 | 2020 | 2375 | 2730 | 3110 | 3385 | 3825 | 4035 | 4200 |
| Static     | 2515 | 3095 | 3640 | 4190 | 4770 | 5185 | 5865 | 6185 | 6440 |

Printed on 4/25/2024 5:59 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..