

MULTIMAX MP 527 - Teknik Özellikler



Description

MULTIMAX MP 527 tarımsal sanayi uygulamalarında teleskopik yükleyiciler ve küçük yükleyiciler için tasarlanmış çok amaçlı bir radyal lastiktir. Lastik, daha sert yüzeylerde bile mükemmel çekiş sağlayan bir blok diş deseni tasarımına sahiptir. Güçlü yanak, kaldırma modunda olağanüstü sabitleme sağlar. MULTIMAX MP 527, kesilme ve kopmaya karşı dirençli özel bir hamura ve uzun bir kullanım ömrüne sahiptir.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Küçük yükleyici • Teleskopik yükleyici
Endüstriyel: Küçük yükleyici • Teleskopik yükleyici

Version	STANDARD
Type	TL
Tyre Size	360/70 R 18 IND
LI/SS	142 A8/B

Dimensions US Standard

Usa code	94053650
Section Width (inch)	14.2
Overall Diameter (inch)	38.1
Static Loaded Radius (inch)	17.3
Rolling Circumference (inch)	113.7
Rim Rec	11
Rim Alt	W10 ; 11 SDC ; W11 ; 12 ; 12 SDC
ECE	E11-106R-002996

Load capacity (lbs)

mph / psi	23	29	35	41	46	51	58	61	64
30	2810	3340	3800	4330	4850	5200	5840	-	-
25	2810	3340	3800	4330	4850	5200	5840	-	-
20	3010	3570	4080	4640	5200	5580	6260	-	-
15	3120	3700	4220	4810	5390	5790	6490	-	-
5 Cyc.	3430	4210	4960	5700	6490	7050	7980	8420	8760
Static	5250	6460	7590	8740	9950	10820	12230	12910	13440

Printed on 4/25/2024 4:28 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..