

MULTIMAX MP 538 - Teknik Özellikler



Description

MULTIMAX MP 538, çeşitli uygulamalar ve makineler için özel olarak tasarlanmış çok amaçlı radyal bir lastiktir: kış koşullarında çalışan greyderler ve yükleyiciler, teleskopik yükleyiciler, yol bakım çalışmalarında kullanılan genel kullanım araçları ve süpürücüler.

MULTIMAX MP 538, güçlü çelik kuşaklı gövdesi sayesinde yüksek hızlarda bile ağır yüklerin taşınmasına olanak tanır. Ayrıca eşsiz sırt tasarımı, buz ve kar üzerinde mükemmel çekişin korunmasına yardımcı olur.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Teleskopik yükleyici • Genel kullanım aracı

Endüstriyel: Greyder • Yükleyici

| | |
|-----------|-----------------|
| Version | STEEL BELTED |
| Type | TL |
| Tyre Size | 405/70 R 20 MPT |
| LI/SS | 152 G |

Dimensions US Standard

| | |
|------------------------------|----------|
| Usa code | 94069682 |
| Section Width (inch) | 16 |
| Overall Diameter (inch) | 42.4 |
| Static Loaded Radius (inch) | 19.1 |
| Rolling Circumference (inch) | 129.5 |
| Rim Rec | W13 |

Load capacity (lbs)

| mph / psi | 87 |
|-----------|------|
| 55 | 7850 |
| 40 | 8500 |
| 25 | 9000 |

Printed on 4/30/2024 3:02 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..