

MULTIMAX MP 540 - Teknik Özellikler



Description

MULTIMAX MP 540, BKT tarafından tüm çok amaçlı araçlar için tasarlanmıştır. Tamçelik gövdesi sayesinde MULTIMAX MP 540, yol içi ve dışı uygulamalar sırasında ağır yüklerin taşınmasını sağlar. Ek olarak, blok diş deseni tasarımı olağanüstü stabilite ve dayanıklılık sağlar.

UM

International Standard

Construction

 RADIAL

Machinery

Zirai: Genel kullanım aracı

Endüstriyel: Genel kullanım aracı / Kompaktör

Version	STANDARD
Type	TL
Tyre Size	335/80 R 18 (12.5 R 18)
LI/SS	132 K

Dimensions International Standard

Overall Width (mm)	340
Overall Diameter (mm)	985
Static Loaded Radius (mm)	446
Rolling Circumference (mm)	3000
Rim Rec	11
ECE	E11-54R-0019559

Load capacity (Kg)

km/h / bar	3.50
110	2000

Printed on 4/26/2024 9:47 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..