

MULTIMAX MP 540 - Teknik Özellikler



Description

MULTIMAX MP 540, BKT tarafından tüm çok amaçlı araçlar için tasarlanmıştır. Tamçelik gövdesi sayesinde MULTIMAX MP 540, yol içi ve dışı uygulamalar sırasında ağır yüklerin taşınmasını sağlar. Ek olarak, blok diş deseni tasarımı olağanüstü stabilite ve dayanıklılık sağlar.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Genel kullanım aracı

Endüstriyel: Genel kullanım aracı / Kompaktör

Version	STANDARD
Type	TL
Tyre Size	405/70 R 20 (16.0/70 R 20)
LI/SS	152 K

Dimensions US Standard

Usa code	94072903
Overall Width (inch)	15.8
Overall Diameter (inch)	42.6
Static Loaded Radius (inch)	19.3
Rolling Circumference (inch)	129.7
Rim Rec	13
Rim Alt	12; 13 SDC

Load capacity (lbs)

mph / psi	87
68	7830

Printed on 4/26/2024 8:03 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..