

MULTIMAX MT 518 - Teknik Özellikler



Description

MULTIMAX MT 518 askeri kamyonlar için özel olarak tasarlanmıştır. Delinmeye karşı yüksek dayanıklılığa ve olağanüstü istikrara sahip, blok desenli ve çelik kuşaklı bir lastiktir. Ayrıca, MULTIMAX MT 518 yüksek hıza dayanır ve uzun bir lastik ömrü sunar.

UM

International Standard

Construction

 RADIAL

Machinery

Endüstriyel: Askeri Kamyon

Version	STANDARD
Type	TL
Tyre Size	36 X 12.5 R 16.5
LI/SS	129 N

Dimensions International Standard

Section Width (mm)	315
Overall Diameter (mm)	902
Static Loaded Radius (mm)	420
Rolling Circumference (mm)	2758
Rim Rec	9.75
ECE	E11-54R-0017917

Load capacity (Kg)

km/h / bar	4.5
140	1850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 6/1/2025 9:30 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..