

## MULTIMAX SR 261 - Teknik Özellikler



### Description

MULTIMAX SR 261; taşıma uygulamalarında ve liman operasyonlarında Düşük Platformlu Römork, Agri Trailer ve Mobil Liman Vinci için özel olarak tasarlanmış, çok katmanlı çelik kuşaklara sahip Tam Çelik bir radyal lastiktir. Güçlü gövdesi ve özel sırt hamuru daha uzun lastik ömrü sağlar. Dişli sırt tasarımı sayesinde MULTIMAX SR 261, tüm uygulamalarda üstün çekiş sağlar. Ayrıca benzersiz 5 RIB sırt tasarımı, eşit sırt aşınması için zemin temasını en üst düzeye çıkarır.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Endüstriyel: Düşük platformlu treyler • Mobil Vinç

Version	STANDARD
Type	TL
Tyre Size	215/75 R 17.5
LI/SS	135/133 J

## Dimensions International Standard

Overall Width (mm)	210
Overall Diameter (mm)	775
Static Loaded Radius (mm)	356
Rolling Circumference (mm)	2371
Rim Rec	6.00
Rim Alt	6.75

## Load capacity (Kg)

	km/h / bar	8.50
100 Load Single		2180
100 Load Dual		2060

Printed on 4/26/2024 5:25 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..