

MULTIMAX SR 261 - Teknik Özellikler



Description

MULTIMAX SR 261; taşıma uygulamalarında ve liman operasyonlarında Düşük Platformlu Römork, Agri Trailer ve Mobil Liman Vinci için özel olarak tasarlanmış, çok katmanlı çelik kuşaklara sahip Tam Çelik bir radyal lastiktir. Güçlü gövdesi ve özel sırt hamuru daha uzun lastik ömrü sağlar. Dişli sırt tasarımı sayesinde MULTIMAX SR 261, tüm uygulamalarda üstün çekiş sağlar. Ayrıca benzersiz 5 RIB sırt tasarımı, eşit sırt aşınması için zemin temasını en üst düzeye çıkarır.

UM

US Standard

Construction

 RADIAL

Machinery

Endüstriyel: Düşük platformlu treyler • Mobil Vinç

Version	STANDARD
Type	TL
Tyre Size	285/70 R 19.5
LI/SS	150/148 J

Dimensions US Standard

Usa code	94067688
Overall Width (inch)	11
Overall Diameter (inch)	35.6
Static Loaded Radius (inch)	16.2
Rolling Circumference (inch)	109.4
Rim Rec	8.25
Rim Alt	7.50 ; 9.00

Load capacity (lbs)

mph / psi	130
62 Load Single	7400
62 Load Dual	6950

Printed on 4/26/2024 9:03 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..