

PAC MASTER PLUS - Teknik Özellikler



Description

PAC MASTER PLUS sıkıştırıcılar için konvansiyonel bir lastiktir. Yüksek derecede istikrar ve geniş temas alanı sunar. Isıya karşı yüksek dayanıklılık sağlayan özel bir bileşikten üretilmiştir. PAC MASTER PLUS uzun bir lastik ömrü sunar.

UM

US Standard

Construction

BIAS

Machinery

Endüstriyel: Kompaktör

Version	STANDARD
Type	TT
Tyre Size	7.50 - 15

Dimensions US Standard

Usa code	94048809
Ply Rating	14
Section Width (inch)	8.9
Overall Diameter (inch)	31.1
Static Loaded Radius (inch)	14.8
Rolling Circumference (inch)	93.9
Rim Rec	6.0
Rim Alt	6.5
ECE	E11-106R-005322

Load capacity (lbs)

mph / psi	127
5	6400
10	5070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 1/19/2025 8:44 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..