

## PAC MASTER - Teknik Özellikler



### Description

PAC MASTER sıkıştırıcılar için konvansiyonel bir lastiktir. Yüksek derecede istikrar ve uzun lastik ömrü sağlar. Özellikle ısıya karşı dayanıklılık sağlayan özel bir bileşikten üretilmiştir.

### UM

US Standard

### Construction

BIAS

### Machinery

Endüstriyel: Kompaktör

Version	SPECIAL
Type	TT
Tyre Size	11.00 - 20

## Dimensions US Standard

Usa code	94067169
Ply Rating	18
Section Width (inch)	11.5
Overall Diameter (inch)	42.1
Static Loaded Radius (inch)	19.4
Rolling Circumference (inch)	130.3
Rim Rec	8.0
Rim Alt	8.5
ECE	E11-106R-006177

## Load capacity (lbs)

mph / psi	120
5	12800
10	10200

Printed on 4/26/2024 11:07 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..