

PAC MASTER - Teknik Özellikler



Description

PAC MASTER sıkıştırıcılar için konvansiyonel bir lastiktir. Yüksek derecede istikrar ve uzun lastik ömrü sağlar. Özellikle ısıya karşı dayanıklılık sağlayan özel bir bileşikten üretilmiştir.

UM

International Standard

Construction

BIAS

Machinery

Endüstriyel: Kompaktör

Version	STANDARD
Type	TL
Tyre Size	9.5/65 - 15

Dimensions International Standard

Ply Rating	6
Section Width (mm)	235
Overall Diameter (mm)	675
Rim Rec	7.0
ECE	E11-106R-005303

Load capacity (Kg)

	km/h / bar	3.25
	10	1320
	15	1060

Printed on 4/26/2024 5:00 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..