

PL 801 - Teknik Özellikler



Description

PL 801 ot biçme uygulamalarında kullanılan döner tırmıklar/ot kurutma makineleri ve ayrıca lojistik operasyonlarında kullanılan forkliftler için özel olarak tasarlanmıştır. Kusursuz istikrarın yanı sıra kesilme ve parçalanmalara karşı yüksek dayanıklılığa sahiptir. PL 801 uzun bir lastik ömrü sunar.

UM

International Standard

Construction

 BIAS

Machinery

Zirai: Saman biçerdöveri • Kuyruk miline bağlı makine •
Forklift
Endüstriyel: Forklift

| | |
|-----------|-----------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 6.50 - 10 |

Dimensions International Standard

| | |
|-----------------------|-----------------|
| Ply Rating | 10 |
| Section Width (mm) | 185 |
| Overall Diameter (mm) | 595 |
| Rim Rec | 5.00 F |
| Rim Alt | 5.50 F |
| ECE | E11-106R-003566 |

Load capacity (Kg)

| | km/h / bar | 7.80 |
|--------------------|------------|------|
| 25 LOAD WHEEL | | 1950 |
| 25 STEER WHEEL | | 1500 |
| 10 OTHER VEHICLES | | 1950 |
| 25 OTHER VEHICLES | | 1500 |
| STATIC SIDE LOADER | | 2265 |

Printed on 4/20/2024 6:23 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..