

PL 801 - Teknik Özellikler



Description

PL 801 ot biçme uygulamalarında kullanılan döner tırmıklar/ot kurutma makineleri ve ayrıca lojistik operasyonlarında kullanılan forkliftler için özel olarak tasarlanmıştır. Kusursuz istikrarın yanı sıra kesilme ve parçalanmalara karşı yüksek dayanıklılığa sahiptir. PL 801 uzun bir lastik ömrü sunar.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Saman biçerdöveri • Kuyruk miline bağlı makine •
Forklift
Endüstriyel: Forklift

Version	STANDARD
Type	TT
Tyre Size	7.00 - 15 (30 X 8 - 15)

Dimensions US Standard

Usa code	94007349
Ply Rating	12
Section Width (inch)	8.1
Overall Diameter (inch)	30.5
Rim Rec	6.0
Rim Alt	5.50 BD ; 5.5

Load capacity (lbs)

mph / psi	125	130
15 LOAD WHEEL	6245	-
15 STEER WHEEL	5275	-
5 OTHER VEHICLES	5275	-
15 OTHER VEHICLES	3885	-
STATIC SIDE LOADER	-	8520

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/11/2025 10:06 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..