

PL 846 - Teknik Özellikler



Description

PL 846 toprak işleme uygulamalarında kullanılan tatbik makineleri için özel olarak tasarlanmıştır. Kusursuz istikrar ve olağanüstü çekiş gücünün yanı sıra kesilme ve parçalanmalara karşı yüksek dayanıklılığa sahiptir. PL 846 kayalık yüzeyler için ideal lastiktir.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Uygulamalı makine

Version	STANDARD
Type	TT
Tyre Size	6.00 - 9

Dimensions US Standard

Usa code	94035915
Ply Rating	12
Section Width (inch)	6.3
Overall Diameter (inch)	21.3
Rim Rec	4.00 E

Load capacity (lbs)

	mph / psi	150
	15	3140

Printed on 4/25/2024 10:00 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..