PORTMAX PM 90 - Teknik Özellikler

Description

PORTMAX PM 90, endüstriyel elleçleme ve çelik işleri de dahil olmak üzere çeşitli uygulamalarda kullanılan konteyner yükleyicileri için özel olarak tasarlanmıştır. Mükemmel dayanıklılık ve sabitleme sağlayan Tamamen Çelik bir radyal lastiktir. Özel antistatik sırt hamuru, özel ısı dayanıklılığı ve daha uzun lastik kullanım ömrü sağlar. PORTMAX PM 90, yuvarlanma direncini azaltarak yakıt ekonomisini iyileştirir.

UM

US Standard

Construction

RADIAL

Machinery

Endüstriyel: Konteyner yükleyici

Version	INDUSTRIAL
Type	TL
Tyre Size	18.00 R 33
LI/SS	214 A5

Dimensions US Standard

Usa code	94057184
Overall Width (inch)	19.1
Overall Diameter (inch)	72.6
Static Loaded Radius (inch)	33.7
Rolling Circumference (inch)	221.4
Rim Rec	13.00/2.50
Rim Alt	13.00/2.50 IF
Star Rating	***

Load capacity (lbs)

mph / psi	145
15	46700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 8:08 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..