

## POWER TRAX HD (FL) - Teknik Özellikler



### Description

POWER TRAX HD endüstriyel uygulamalarda forklift ekipmanı için özel olarak tasarlanmış, üstün çapraz katlı bir lastiktir. Derin sırt, ekstra kalın yanak ve sağlam gövde olağanüstü dayanıklılık sağlayarak delinme ve kazaen oluşan hasar riskini en aza indirir. Lastik, pürüzlü ve sert beton yüzeylere uygun kesilme, kopma ve yırtılma direncine sahiptir. Özel olarak tasarlanmış jant koruyucusu, jant flanşı bölgesinde lastik patlamalarına ve tekerlek hasarlarına karşı koruma sağlar.

### UM

US Standard

### Construction

BIAS

### Machinery

Endüstriyel: Forklift

Version	IMPLEMENT
Type	TT
Tyre Size	10.00 - 20
LI/SS	160 A8

## Dimensions US Standard

Usa code	94058068
Ply Rating	16
Section Width (inch)	11.2
Overall Diameter (inch)	42.5
Rim Rec	7.5
Rim Alt	8.0
ECE	E11-106R-003664

## Load capacity (lbs)

mph / psi	131
25	9900

Printed on 4/28/2024 3:57 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..