

## POWER TRAX HD (FL) - Teknik Özellikler



### Description

POWER TRAX HD endüstriyel uygulamalarda forklift ekipmanı için özel olarak tasarlanmış, üstün çapraz katlı bir lastiktir. Derin sırt, ekstra kalın yanak ve sağlam gövde olağanüstü dayanıklılık sağlayarak delinme ve kazaen oluşan hasar riskini en aza indirir. Lastik, pürüzlü ve sert beton yüzeylere uygun kesilme, kopma ve yırtılma direncine sahiptir. Özel olarak tasarlanmış jant koruyucusu, jant flanşı bölgesinde lastik patlamalarına ve tekerlek hasarlarına karşı koruma sağlar.

### UM

US Standard

### Construction

BIAS

### Machinery

Endüstriyel: Forklift

Version	STANDARD
Type	TT
Tyre Size	6.50 - 10

## Dimensions US Standard

Usa code	94007813
Ply Rating	10
Section Width (inch)	7.6
Overall Diameter (inch)	23.4
Static Loaded Radius (inch)	10.9
Rolling Circumference (inch)	69.8
Rim Rec	5.00 F
Rim Alt	5.50 F

## Load capacity (lbs)

mph / psi	112
15 LOAD WHEEL	4300
15 STEER WHEEL	3305
5 OTHER VEHICLES	4300
15 OTHER VEHICLES	3305
STATIC SIDE LOADER	4995

Printed on 4/28/2024 3:21 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..