

## POWER TRAX HD (SS) - Teknik Özellikler



### Description

POWER TRAX HD liman ve yeraltı maden işletmesi uygulamalarındaki ekipmanlar için özel olarak tasarlanmış, üstün bir lastiktir. Derin sırtı, ekstra kalın yanağı ve sağlam gövdesi olağanüstü dayanıklılık sağlayarak delinme ve kazaen oluşan hasar riskini en aza indirir. Lastik, özellikle pürüzlü ve sert beton yüzeylere uygun kesilme ve kopma direncine sahiptir. Özel olarak tasarlanmış jant koruyucusu, jant flanşı bölgesinde lastik patlamalarına ve tekerlek hasarına karşı koruma sağlar.

### UM

US Standard

### Construction

BIAS

### Machinery

Endüstriyel: Mini yükleyici

Version	STANDARD
Type	TL
Tyre Size	12 - 16.5

## Dimensions US Standard

Usa code	94017331
Ply Rating	10
Section Width (inch)	12.8
Overall Diameter (inch)	34.1
Static Loaded Radius (inch)	15.4
Rolling Circumference (inch)	100.5
Rim Rec	9.75

## Load capacity (lbs)

	mph / psi	65
	5	5600
	10	4420
	15	4090

Printed on 4/24/2024 3:58 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..