

POWER TRAX HD (SS) - Teknik Özellikler



Description

POWER TRAX HD liman ve yeraltı maden işletmesi uygulamalarındaki ekipmanlar için özel olarak tasarlanmış, üstün bir lastiktir. Derin sırtı, ekstra kalın yanağı ve sağlam gövdesi olağanüstü dayanıklılık sağlayarak delinme ve kazaen oluşan hasar riskini en aza indirir. Lastik, özellikle pürüzlü ve sert beton yüzeylere uygun kesilme ve kopma direncine sahiptir. Özel olarak tasarlanmış jant koruyucusu, jant flanşı bölgesinde lastik patlamalarına ve tekerlek hasarına karşı koruma sağlar.

UM

International Standard

Construction

BIAS

Machinery

Endüstriyel: Mini yükleyici

Version	STANDARD
Type	TL
Tyre Size	12 - 16.5

Dimensions International Standard

Ply Rating	14
Section Width (mm)	324
Overall Diameter (mm)	865
Static Loaded Radius (mm)	391
Rolling Circumference (mm)	2552
Rim Rec	9.75
ECE	E11-106R-005562

Load capacity (Kg)

	km/h / bar	6.20
	10	3075
	15	2430
	25	2245

Printed on 4/24/2024 5:41 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..