

POWER TRAX HD - Teknik Özellikler



Description

POWER TRAX HD liman ve yeraltı maden işletmesi uygulamalarındaki ekipmanlar için özel olarak tasarlanmış, üstün bir lastiktir. Derin sırtı, ekstra kalın yanağı ve sağlam gövdesi olağanüstü dayanıklılık sağlayarak delinme ve kazaen oluşan hasar riskini en aza indirir. Lastik, özellikle pürüzlü ve sert beton yüzeylere uygun kesilme ve kopma direncine sahiptir. Özel olarak tasarlanmış jant koruyucusu, jant flanş bölgesinde lastik patlamalarına ve tekerlek hasarına karşı koruma sağlar.

UM

International Standard

Construction

BIAS

Machinery

Endüstriyel: Konteyner taşıyıcı
Yoldışı: Yeraltı madenciliği aracı

Version	STANDARD
Type	TT
Tyre Size	12.00 - 20

Dimensions International Standard

Ply Rating	28
Section Width (mm)	320
Overall Diameter (mm)	1150
Rim Rec	8.50
Rim Alt	9.0

Load capacity (Kg)

km/h / bar	10.00
25 LOAD WHEEL	9490
25 STEER WHEEL	7300
10 OTHER VEHICLES	9490
25 OTHER VEHICLES	7300
STATIC SIDE LOADER	11025

Printed on 4/17/2024 3:49 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..