

PRO RIB F2M - Teknik Özellikler



Description

PRO RIB F2M, toprak işleme uygulamalarında kullanılan tek çeker traktörler için tarımsal bir lastiktir. Özellikle, yüksek seviyede elleçleme gerektiren tüm işlemler için uygundur.

UM

US Standard

Construction

 BIAS

Machinery

Zirai: Tek çeker traktör
Endüstriyel: Römork

Version	INDUSTRIAL
Type	TT
Tyre Size	10.00 - 16 SL
LI/SS	110 A8

Dimensions US Standard

Usa code	94055081
Ply Rating	8
Section Width (inch)	10.8
Overall Diameter (inch)	35.2
Static Loaded Radius (inch)	16.1
Rolling Circumference (inch)	103.1
Rim Rec	8 LB
Rim Alt	W 8 L
ECE	E11-106R-005290
TRA Code	F2M

Load capacity (lbs)

mph / psi	44
25	2340

Printed on 4/24/2024 8:36 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..