

## PRO RIB F2M - Teknik Özellikler



### Description

PRO RIB F2M, toprak işleme uygulamalarında kullanılan tek çeker traktörler için tarımsal bir lastiktir. Özellikle, yüksek seviyede elleçleme gerektiren tüm işlemler için uygundur.

### UM

International Standard

### Construction

 BIAS

### Machinery

Zirai: Tek çeker traktör  
Endüstriyel: Römork

Version	STANDARD
Type	TL
Tyre Size	16.5L - 16.1 SL
LI/SS	129 A8

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	430
Overall Diameter (mm)	1072
Rim Rec	W 14 C
Rim Alt	W 14 CH
ECE	E11-106R-007860
TRA Code	F2M

## Load capacity (Kg)

km/h / bar	2.80
40	1850

Printed on 4/24/2024 5:58 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..