

PUDDLE SPECIAL (A) - Teknik Özellikler



Description

PUDDLE SPECIAL çeltik tarlalarındaki çalışmalar için özel olarak tasarlanmış bir R-2 tarım lastiğidir. Ekstra derin dişler ile özel çekme deseni, ıslak ve yumuşak toprakta bile kusursuz çekiş gücü ve en iyi tutuşu sağlar. Geniş merkez çubuğu, yol uygulamalarına daha iyi uyum kabiliyeti ve olağanüstü hizmet performansı sağlar. Ek olarak, PUDDLE SPECIAL üstün kendini temizleme özelliklerine ve kusursuz sağlamlığa sahiptir.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Traktör

Version	STANDARD
Type	TL
Tyre Size	11 - 32
LI/SS	111 A2

Dimensions International Standard

Ply Rating	6
Section Width (mm)	305
Overall Diameter (mm)	1465
Static Loaded Radius (mm)	702
Rolling Circumference (mm)	4384
Rim Rec	W 10
Rim Alt	W 9
ECE	E11-106R-004096
TRA Code	R2+

Load capacity (Kg)

km/h / bar	1.60
10	1080

Printed on 4/20/2024 3:55 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..