

## PUDDLE SPECIAL (A) - Teknik Özellikler



### Description

PUDDLE SPECIAL çeltik tarlalarındaki çalışmalar için özel olarak tasarlanmış bir R-2 tarım lastiğidir. Ekstra derin dişler ile özel çekme deseni, ıslak ve yumuşak toprakta bile kusursuz çekiş gücü ve en iyi tutuşu sağlar. Geniş merkez çubuğu, yol uygulamalarına daha iyi uyum kabiliyeti ve olağanüstü hizmet performansı sağlar. Ek olarak, PUDDLE SPECIAL üstün kendini temizleme özelliklerine ve kusursuz sağlamlığa sahiptir.

### UM

International Standard

### Construction

 BIAS

### Machinery

Zirai: Traktör

Version	STANDARD
Type	TT
Tyre Size	12.4 - 28
LI/SS	137 A2

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	325
Overall Diameter (mm)	1385
Static Loaded Radius (mm)	649
Rolling Circumference (mm)	4067
Rim Rec	W 11
Rim Alt	W 10
TRA Code	R2+

## Load capacity (Kg)

km/h / bar	3.50
10	2300

Printed on 4/20/2024 4:00 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..