

PUDDLE SPECIAL (B) - Teknik Özellikler



Description

PUDDLE SPECIAL çeltik tarlalarındaki çalışmalar için özel olarak tasarlanmış bir R-2 tarım lastiğiidir. Ekstra derin dişler ile özel çekme deseni, ıslak ve yumuşak toprakta bile kusursuz çekiş gücü ve en iyi tutuşu sağlar. Geniş merkez çubuğu, yol uygulamalarına daha iyi uyum kabiliyeti ve olağanüstü hizmet performansı sağlar. Ek olarak, PUDDLE SPECIAL üstün kendini temizleme özelliklerine ve kusursuz sağlamlılığa sahiptir.

UM

US Standard

Construction

❖ BIAS

Machinery

Zirai: İlaçlama

Version	STANDARD
Type	TL
Tyre Size	120/90 - 26
LI/SS	90 A2

Dimensions US Standard

Usa code	94059638
Ply Rating	6
Section Width (inch)	5
Overall Diameter (inch)	37
Static Loaded Radius (inch)	17.6
Rolling Circumference (inch)	112.1
Rim Rec	4 JA

ECE E11-106R-005236

Load capacity (lbs)

mph / psi	44
5	1320

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 6/1/2025 10:23 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..