

RIB 324 - Teknik Özellikler



Description

RIB 324, gevşek toprak ve kumlu arazide en iyi stabilite ve yüzdürme özelliklerini sağlamak için özel bir blok sırt deseni ve geniş bir temas alanı ile tasarlanmıştır. Güçlü naylon gövde ve yanak, özel bir sırt hamuru ile birlikte, delinmelere ve aşınmaya karşı mükemmel direncin yanı sıra daha yüksek yük kapasitesi sağlar.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Uygulamalı makine
Endüstriyel: Römork

Version	STANDARD
Type	TL
Tyre Size	66 X 44.00 - 25

Dimensions International Standard

Ply Rating	20
Section Width (mm)	1110
Overall Diameter (mm)	1700
Rim Rec	36.0 TH

Load capacity (Kg)

km/h / bar	3.50
50	7300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 1/13/2025 8:45 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..