

RIB 774 (A) - Teknik Özellikler



Description

RIB 774 (A) är ett redskapsdäck med låga sektioner som erbjuder hög lastkapacitet och lång livslängd. Det lämpar sig för höskördning och transporttillämpningar med balpress och släpvagn.

UM

US Standard

Construction

 BIAS

Machinery

Zirai: Balya makinesi • Saman biçerdöveri • Römork

Version	STANDARD
Type	TL
Tyre Size	250/65 - 14.5
LI/SS FREE ROLLING	119 A8

Dimensions US Standard

Usa code	94027248
Ply Rating	12
Section Width (inch)	10
Overall Diameter (inch)	27.2
Static Loaded Radius (inch)	11.9
Rolling Circumference (inch)	77.9
Rim Rec	AG 8.00
Rim Alt	6.75
ECE	E11-106R-003532

Load capacity (lbs)

mph / psi	68
5 FR	4200
15 FR	3570
20 FR	3360
25 FR	3000

Printed on 4/26/2024 6:02 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..