

RIB 774 (A) - Teknik Özellikler



Description

RIB 774 (A) är ett redskapsdäck med låga sektioner som erbjuder hög lastkapacitet och lång livslängd. Det lämpar sig för höskördning och transporttillämpningar med balpress och släpvagn.

UM

International Standard

Construction

 BIAS

Machinery

Zirai: Balya makinesi • Saman biçerdöveri • Römork

Version	STANDARD
Type	TL
Tyre Size	250/65 - 14.5
LI/SS FREE ROLLING	124 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	255
Overall Diameter (mm)	690
Static Loaded Radius (mm)	303
Rolling Circumference (mm)	1978
Rim Rec	AG 8.00
Rim Alt	6.75
ECE	E11-106R-003374

Load capacity (Kg)

	km/h / bar	5.50
	10 FR	2240
	25 FR	1905
	30 FR	1790
	40 FR	1600

Printed on 4/26/2024 6:47 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..