

RIB 774 (B) - Teknik Özellikler



Description

RIB 774 (B) alçak kesitli bir uygulama lastiğidir. Modern tarım için idealdir ve uygulamalı makineler ve römorklar ile yolda ve yol dışında uygulamalar için idealdir. Mükemmel yük kapasitesi ve uzun bir lastik kullanım ömrü sunar. Ağır hizmet için "HD" versiyonu da mevcuttur.

UM

International Standard

Construction

 BIAS

Machinery

Zirai: Uygulamalı makine • Römork
Endüstriyel: Römork

Version	STANDARD
Type	TL
Tyre Size	15.0/55 - 17
LI/SS FREE ROLLING	141 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	391
Overall Diameter (mm)	850
Static Loaded Radius (mm)	377
Rolling Circumference (mm)	2490
Rim Rec	13.00
Rim Alt	13
ECE	E11-106R-004311

Load capacity (Kg)

km/h / bar	3.70
10 FR	3605
25 FR	3065
30 FR	2885
40 FR	2575

Printed on 4/19/2024 11:02 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..