

RIB 774 (B) - Teknik Özellikler



Description

RIB 774 (B) alçak kesitli bir uygulama lastiğidir. Modern tarım için idealdir ve uygulamalı makineler ve römorklar ile yolda ve yol dışında uygulamalar için idealdir. Mükemmel yük kapasitesi ve uzun bir lastik kullanım ömrü sunar. Ağır hizmet için "HD" versiyonu da mevcuttur.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Uygulamalı makine • Römork
Endüstriyel: Römork

Version	STANDARD
Type	TL
Tyre Size	15.0/55 - 17
LI/SS FREE ROLLING	134 A8

Dimensions US Standard

Usa code	94010936
Ply Rating	10
Section Width (inch)	15.4
Overall Diameter (inch)	33.5
Static Loaded Radius (inch)	14.8
Rolling Circumference (inch)	98
Rim Rec	13.00
Rim Alt	13
ECE	E11-106R-004309

Load capacity (lbs)

mph / psi	38
5 FR	6550
15 FR	5570
20 FR	5240
25 FR	4670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/7/2024 7:45 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..