

## RIB 774 (C) - Teknik Özellikler



### Description

RIB 774 (C) alçak kesitli ve dar bir uygulama lastiğidir. Hem yolda hem yol dışında balyalama makineleri ve römorklar ile saman hasadı ve taşıma uygulamaları için idealdir. Mükemmel yük kapasitesi ve uzun bir lastik kullanım ömrü sunar.

### UM

US Standard

### Construction

BIAS

### Machinery

Zirai: Balya makinesi • Saman biçerdöveri • Römork

|                    |              |
|--------------------|--------------|
| Version            | STANDARD     |
| Type               | TL           |
| Tyre Size          | 19.0/45 - 17 |
| LI/SS FREE ROLLING | 138 A8       |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94027330        |
| Ply Rating                   | 10              |
| Section Width (inch)         | 17.9            |
| Overall Diameter (inch)      | 33.3            |
| Static Loaded Radius (inch)  | 15.2            |
| Rolling Circumference (inch) | 99.1            |
| Rim Rec                      | 16.00           |
| ECE                          | E11-106R-004589 |

## Load capacity (lbs)

| mph / psi | 33   |
|-----------|------|
| 5 FR      | 7290 |
| 15 FR     | 6190 |
| 20 FR     | 5830 |
| 25 FR     | 5200 |

Printed on 4/13/2024 8:50 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..