

RIB 774 (C) - Teknik Özellikler



Description

RIB 774 (C) alçak kesitli ve dar bir uygulama lastiğidir. Hem yolda hem yol dışında balyalama makineleri ve römorklar ile saman hasadı ve taşıma uygulamaları için idealdir. Mükemmel yük kapasitesi ve uzun bir lastik kullanım ömrü sunar.

UM

US Standard

Construction

BIAS

Machinery

Zirai: Balya makinesi • Saman biçerdöveri • Römork

Version	STANDARD
Type	TL
Tyre Size	215/75 - 17.5
LI/SS FREE ROLLING	134 A8

Dimensions US Standard

Usa code	94011001
Ply Rating	12
Section Width (inch)	8.7
Overall Diameter (inch)	30.5
Static Loaded Radius (inch)	14.2
Rolling Circumference (inch)	90.9
Rim Rec	6.75
ECE	E11-106R-004590

Load capacity (lbs)

mph / psi	100
5 FR	6550
15 FR	5570
20 FR	5240
25 FR	4670

Printed on 4/22/2024 11:50 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..