

RIB F3 - Veri Sayfasını İndir



Description

RIB F3, toprak işleme ve taşıma operasyonlarında kullanılan tek çeker traktörler için tasarlanmış, araziye yönelik bir lastiktir. Bazı ebatlar römork kullanılan taşıma uygulamaları için uygundur. RIB F3 lastik, yüksek seviye elleçleme gerektiren tüm operasyonlar için ideal bir ortaktır. Mükemmel dayanıklılık ve anız direnci sağlamak için sert bir hamur ile tasarlanmıştır.

UM

International Standard

Construction

BIAS

Machinery

Zirai: Tek çeker traktör • Römork

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
9.00 - 16	HD	F3	120 A6/ 112 A8	12	W 8	6.00 F ; W 7 ; W 8 L	245	878	387	2573	TT	E11-106R-004658
9.00 - 16	STANDARD	F3	120 A6/ 112 A8	12	W 8	6.00 F ; W 7 ; W 8 L	245	878	387	2573	TT	E11-106R-004592
9.00 - 16	STANDARD	F3	120 A6/ 112 A8	12	W 8	6.00 F ; W 7 ; W 8 L	245	878	387	2573	TL	E11-106R-004592

Printed on 4/19/2024 4:26 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..