

RIB IMPLEMENT (A) - Teknik Özellikler



Description

RIB IMPLEMENT (A) taşımacılık ve toprak işleme uygulamalarında römorklar ve uygulamalı makineler için geliştirilmiştir. Modern çiftçilik için idealdir ve hem yolda hem de yol dışında üstün performans gösterir. RIB IMPLEMENT (A) mahsulleri korumak amacıyla yüksek bir kullanım seviyesi ve azalan toprak sıkıştırması gerektiren tüm çalışma koşulları için doğru seçimdir.

UM

International Standard

Construction

 BIAS

Machinery

Zirai: Uygulamalı makine • Römork

Version	STANDARD
Type	TL
Tyre Size	10.0/80 - 12
LI/SS FREE ROLLING	110 A8

Dimensions International Standard

Ply Rating	6
Section Width (mm)	264
Overall Diameter (mm)	746
Static Loaded Radius (mm)	329
Rolling Circumference (mm)	2186
Rim Rec	9.00
Rim Alt	7.0
ECE	E11-106R-003533

Load capacity (Kg)

km/h / bar	2.30
10 FR	1485
25 FR	1260
30 FR	1185
40 FR	1060

Printed on 4/27/2024 9:12 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..