

RIB IMPLEMENT (B) - Teknik Özellikler



Description

RIB IMPLEMENT (B) özellikle tarım uygulamaları için tasarlanmıştır. Modern çiftçilik için ideal olan lastik, delinmeye karşı mükemmel koruma sağlayan anızlara dirençli bir hamurdan üretilmiştir. RIB IMPLEMENT (B) daha uzun hizmet ömrü için güçlü bir gövdeye sahip 5 kuşaklı sırt deseni olan bir lastiktir. Yüksek yük kapasitesiyle birlikte düşük yuvarlanma direci gerektiren tüm çalışma koşulları için doğru seçimdir.

UM

International Standard

Construction

 BIAS

Machinery

Zirai: Uygulamalı makine

Version	STANDARD
Type	TT
Tyre Size	49 - 17
LI/SS DRIVE WHEEL	146 A8/143 B
LI/SS FREE ROLLING	158 A8/154 B

Dimensions International Standard

Ply Rating	20
Section Width (mm)	425
Overall Diameter (mm)	1200
Rim Rec	13.0
Rim Alt	14.0
ECE	E11-106R-004653

Load capacity (Kg)

	km/h / bar	4.0
	40 FR	4250
	50 FR	3750
	40 DW	3000
	50 DW	2725

Printed on 11/28/2023 6:21 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..