

RIDEMAX FL 690 - Teknik Özellikler



Description

RIDEMAX FL 690, tanker kamyonlar ve römorklar için radyal bir yayılma ve taşıma lastiğidir. Lastik, %75 oranında yol uygulamaları için uygundur. Modern tarımda artan yüksek yük talebine yanıt olarak BKT, bu çelik kuşaklı lastiği çok ağır yüklere dayanacak ve çiftçinin üretkenliğini artıracak şekilde tasarlamıştır. Düşük yuvarlanma direnci daha iyi yakıt ekonomisine katkıda bulunur.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Tanker • Römork

Endüstriyel: Römork

| | |
|-----------|---------------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 28L R 26 (750/65 R 26) |
| LI/SS | 176 A8/173 B |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94034321 |
| Section Width (inch) | 28.3 |
| Overall Diameter (inch) | 62.6 |
| Static Loaded Radius (inch) | 27.4 |
| Rolling Circumference (inch) | 186.8 |
| Rim Rec | DW 25 B |
| Rim Alt | DW 23 B |
| ECE | E11-106R-002985 |

Load capacity (lbs)

| mph / psi | 12 | 15 | 20 | 23 | 29 | 35 | 41 |
|-----------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 6880 | 7850 | 9530 | 10320 | 11750 | 13040 | 14330 |
| 25 | 7520 | 8560 | 10420 | 11280 | 12840 | 14250 | 15650 |
| 20 | 8420 | 9600 | 11670 | 12630 | 14380 | 15960 | 17540 |
| 15 | 8950 | 10200 | 12390 | 13410 | 15280 | 16950 | 18630 |
| 5 | 10530 | 11990 | 14580 | 15780 | 17980 | 19950 | 21910 |

Printed on 4/17/2024 5:05 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..