

RIDEMAX FL 693 M - Teknik Özellikler



Description

RIDEMAX FL 693 M, sıklıkla römork/tanker kamyonlarla yolda seyahat edenler için ideal bir radyal lastiktir. %75 yolda kullanım için tasarlanan RIDEMAX FL 693 M, hem konfor hem de kendi kendini temizleme özelliklerine öncelik vererek mükemmel yol performansı sağlar. Serinin D/E hız endeksi sınıfları, yolda seyahat ederken daha yüksek hızları temsil eder ve bu da önemli ölçüde zaman tasarrufu sağlar. Düşük yuvarlanma direnci daha az yakıt tüketimine katkıda bulunurken, güçlendirilmiş bir damak ve çelik kuşaklar daha fazla dayanıklılık sağlar.

UM

International Standard

Construction

 RADIAL

Machinery

Zirai: Tanker • Römork

Version	STANDARD
Type	TL
Tyre Size	560/55 R 22.5
LI/SS	158 D/155 E

Dimensions International Standard

Section Width (mm)	543
Overall Diameter (mm)	1180
Static Loaded Radius (mm)	533
Rolling Circumference (mm)	3614
SRI (mm)	550
Rim Rec	AG 16.00
Rim Alt	17.00 ; 20.00
ECE	E4-106R-000631

Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1435	1630	1940	2290	2620	2910	3255	3565	3875
65	1575	1785	2125	2510	2870	3190	3570	3910	4250
50	1910	2165	2575	3040	3475	3860	4325	4735	5145
40	2140	2430	2890	3415	3905	4335	4860	5320	5780
25	2490	2825	3360	3965	4535	5040	5645	6180	6715
10	2835	3215	3825	4515	5165	5740	6430	7040	7650

Printed on 4/30/2024 3:17 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..