

## RIDEMAX FL 693 M - Teknik Özellikler



### Description

RIDEMAX FL 693 M, sıklıkla römork/tanker kamyonlarla yolda seyahat edenler için ideal bir radyal lastiktir. %75 yolda kullanım için tasarlanan RIDEMAX FL 693 M, hem konfor hem de kendi kendini temizleme özelliklerine öncelik vererek mükemmel yol performansı sağlar. Serinin D/E hız endeksi sınıfları, yolda seyahat ederken daha yüksek hızları temsil eder ve bu da önemli ölçüde zaman tasarrufu sağlar. Düşük yuvarlanma direnci daha az yakıt tüketimine katkıda bulunurken, güçlendirilmiş bir damak ve çelik kuşaklar daha fazla dayanıklılık sağlar.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Zirai: Tanker • Römork

Version	STANDARD
Type	TL
Tyre Size	710/50 R 26.5
LI/SS	170 D

## Dimensions US Standard

Usa code	94037315
Section Width (inch)	28.6
Overall Diameter (inch)	54.4
Static Loaded Radius (inch)	24.6
Rolling Circumference (inch)	166
Rim Rec	AG 24.00
Rim Alt	AG 20.00
ECE	E4-106R-001422

## Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	4450	5050	6130	7100	8180	9260	9980	11060	12010
40	4890	5560	6750	7800	8990	10180	10980	12170	13230
30	5930	6720	8170	9450	10890	12330	13290	14730	16000
25	6670	7560	9180	10610	12230	13860	14940	16560	17990
15	7740	8780	10660	12330	14220	16090	17350	19230	20900
5	8820	10010	12150	14050	16190	18340	19760	21910	23810

Printed on 4/29/2024 4:36 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..