

RIDEMAX IT 696 - Teknik Özellikler



Description

RIDEMAX IT 696, benzersiz bir sırt tasarımına ve kış koşullarında bile yol uygulamaları için mükemmel kavrama sağlayan geniş bir taban izine sahiptir. Lastik, yüksek hız özelliği ve güçlü gövdesi sayesinde taşıma ve belediye/bakım uygulamaları için en uygun lastiktir. Sırt tasarımı, ağır hizmetler için özellikle geliştirilmiştir ve yakıt ekonomisiyle birlikte mükemmel sabitleme sağlayan düşük yuvarlanma direnci sunar.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Traktör

| | |
|-----------|--------------------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 340/80 R 24 IND (12.4 R 24) |
| LI/SS | 140 A8/135 D |

Dimensions US Standard

| | |
|------------------------------|---------------------|
| Usa code | 94033843 |
| Section Width (inch) | 13.5 |
| Overall Diameter (inch) | 45.4 |
| Static Loaded Radius (inch) | 20.5 |
| Rolling Circumference (inch) | 135.6 |
| Rim Rec | DW 11 |
| Rim Alt | W 10 ; W 12 ; DW 10 |
| ECE | E4-106R-002293 |

Load capacity (lbs)

| mph / psi | 17 | 23 | 29 | 35 | 41 | 46 |
|-----------|------|------|------|------|------|------|
| 40 | 2260 | 2790 | 3260 | 3790 | 4280 | 4810 |
| 30 | 2440 | 3010 | 3530 | 4090 | 4610 | 5180 |
| 25 | 2590 | 3200 | 3750 | 4350 | 4910 | 5510 |
| 20 | 2690 | 3330 | 3900 | 4530 | 5100 | 5730 |

Printed on 4/20/2024 6:16 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..