

RIDEMAX IT 696 - Teknik Özellikler



Description

RIDEMAX IT 696, benzersiz bir sırt tasarımına ve kış koşullarında bile yol uygulamaları için mükemmel kavrama sağlayan geniş bir taban izine sahiptir. Lastik, yüksek hız özelliği ve güçlü gövdesi sayesinde taşıma ve belediye/bakım uygulamaları için en uygun lastiktir. Sırt tasarımı, ağır hizmetler için özellikle geliştirilmiştir ve yakıt ekonomisiyle birlikte mükemmel sabitleme sağlayan düşük yuvarlanma direnci sunar.

UM

International Standard

Construction

 RADIAL

Machinery

Zirai: Traktör

Version	STANDARD
Type	TL
Tyre Size	360/80 R 24 IND (13.6 R 24)
LI/SS	143 A8/138 D

Dimensions International Standard

Section Width (mm)	343
Overall Diameter (mm)	1186
Static Loaded Radius (mm)	537
Rolling Circumference (mm)	3556
SRI (mm)	575
Rim Rec	DW 11
Rim Alt	W 12 ; W 10
ECE	E11-106R-004753

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	1110	1370	1605	1865	2100	2360
50	1200	1480	1735	2015	2270	2550
40	1280	1580	1855	2155	2425	2725
30	1535	1895	2225	2585	2910	3270

Printed on 4/23/2024 9:18 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..