

RIDEMAX IT 696 - Teknik Özellikler



Description

RIDEMAX IT 696, benzersiz bir sırt tasarımına ve kış koşullarında bile yol uygulamaları için mükemmel kavrama sağlayan geniş bir taban izine sahiptir. Lastik, yüksek hız özelliği ve güçlü gövdesi sayesinde taşıma ve belediye/bakım uygulamaları için en uygun lastiktir. Sırt tasarımı, ağır hizmetler için özellikle geliştirilmiştir ve yakıt ekonomisiyle birlikte mükemmel sabitleme sağlayan düşük yuvarlanma direnci sunar.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Traktör

Version	STANDARD
Type	TL
Tyre Size	360/80 R 24 IND (13.6 R 24)
LI/SS	143 A8/138 D

Dimensions US Standard

Usa code	94057252
Section Width (inch)	13.5
Overall Diameter (inch)	46.7
Static Loaded Radius (inch)	21.1
Rolling Circumference (inch)	140
Rim Rec	DW 11
Rim Alt	W 12 ; W 10
ECE	E11-106R-004753

Load capacity (lbs)

mph / psi	17	23	29	35	41	46
40	2450	3020	3540	4110	4630	5200
30	2650	3260	3820	4440	5000	5620
25	2820	3480	4090	4750	5350	6010
20	3380	4180	4910	5700	6420	7210

Printed on 4/23/2024 10:40 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..