

RIDEMAX IT 696 - Teknik Özellikler



Description

RIDEMAX IT 696, benzersiz bir sırt tasarımına ve kış koşullarında bile yol uygulamaları için mükemmel kavrama sağlayan geniş bir taban izine sahiptir. Lastik, yüksek hız özelliği ve güçlü gövdesi sayesinde taşıma ve belediye/bakım uygulamaları için en uygun lastiktir. Sırt tasarımı, ağır hizmetler için özellikle geliştirilmiştir ve yakıt ekonomisiyle birlikte mükemmel sabitleme sağlayan düşük yuvarlanma direnci sunar.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Traktör

Version	STANDARD
Type	TL
Tyre Size	400/80 R 28 IND (14.9 R 28)
LI/SS	151 A8/146 D

Dimensions US Standard

Usa code	94039227
Section Width (inch)	15.9
Overall Diameter (inch)	53.2
Static Loaded Radius (inch)	24.2
Rolling Circumference (inch)	159.4
Rim Rec	W 13
Rim Alt	W 12 ; W 14 L
ECE	E4-106R-002401

Load capacity (lbs)

mph / psi	17	23	29	35	41	46
40	3110	3840	4500	5220	5890	6610
30	3370	4170	4880	5680	6390	7190
25	3570	4410	5170	6010	6770	7610
20	3730	4610	5400	6270	7070	7940

Printed on 4/23/2024 9:54 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..